

3/4-10 UNC - 2B $\overline{\lor}$.75 \lfloor 19.1 \rfloor		
DER HEAD (MAINTENANCE) ONLY.— HOLE FOR LIFTING COMPRESSOR!	[482.6] 19.00 [419.1] 16.50	3/4-10 UNC - 2B $\sqrt{}$.75[19.1] THIS IS A LIFTING HOLE FOR CYLINDER HEAD (MAINDO NOT USE THIS HOLE FOR LIFTING COMPRESSOR
[584.2] [520.7] 23.00 20.50		D3 NOTE 5
		NOTES:

4X ∅ 1.00[25.4] THRU

	NOZZLE CONNECTIONS	BOLT HOLE SIZE
N1	6" GAS SUCTION FLANGE (ANSI CLASS 150 FLAT FACE)	8 x 3/4-10
N2	4" GAS DISCHARGE FLANGE (ANSI CLASS 150 FLAT FACE)	8 x 5/8-11
W1A	2 NPT(F) WATER INLET (SEE NOTE 2)	N/A
W1B	2 NPT(F) WATER INLET (SEE NOTE 2)	N/A
W2	1-1/2 NPT(F) WATER OUTLET	N/A
D1	1-1/4 NPT(F) DRAIN HOLE	N/A
D2	1-1/4 NPT(F) DRAIN HOLE	N/A
D3	1/8 NPT (F) SEAL WEEPAGE DRAIN	N/A

OIL CONNECTION POINTS SUMMARY				
(REFER TO MANUAL FOR FURTHER INFORMATION)				
DESCRIPTION	THREAD SIZE	QTY		
LUBE QUILL(LQx)	1/4 NPT (F)	1		
LUBE POINTS (LPx)	1/4 NPT (F)	6		

1. - CENTER OF MASS DIMENSIONS ARE APPROXIMATE

- 2. EITHER WATER INLET MAY BE USED, DEPENDING UPON SYSTEM NEEDS
- 3. WEIGHT IS APPROXIMATE
- 4. THIS DRAWING IS DUAL DIMENSION. DIMENSIONS WITHOUT BRACKETS ARE IN INCHES, DIMENSIONS IN [BRACKETS] ARE IN MILLIMETERS.
- 5. REMOVE (3) RED SEAL LOCKING TABS BEFORE OPERATION. RETAIN TABS AND SCREWS FOR SERVICE (TABS MUST BE INSTALLED BEFORE SEAL REMOVAL).

PROPRIETARY AND CONFIDENTIAL

