



- NOTES:
1. CENTER OF MASS DIMENSIONS ARE APPROXIMATE
 2. EITHER WATER INLET MAY BE USED, DEPENDING UPON SYSTEM NEEDS
 3. WEIGHT IS APPROXIMATE
 4. DRAWING IS DUAL DIMENSION. DIMENSIONS WITHOUT BRACKETS ARE IN INCHES. DIMENSIONS IN [BRACKETS] ARE IN MILLIMETERS.

NOZZLE CONNECTIONS		BOLT HOLE SIZE
N1	3" GAS SUCTION FLANGE (ANSI CLASS 150 FLAT FACE)	4 x 5/8-11 ∇ 1.00
N2	3" GAS DISCHARGE FLANGE (ANSI CLASS 150 FLAT FACE)	4 x 5/8-11 ∇ 1.00
W1A	1-1/4 NPT(F) WATER INLET (SEE NOTE 2)	N/A
W1B	1/2 NPT(F) WATER INLET (SEE NOTE 2)	N/A
W2	1-1/4 NPT(F) WATER OUTLET	N/A
D1	1/4 NPT DRAIN HOLE	N/A

OIL CONNECTION POINTS SUMMARY		
(REFER TO MANUAL FOR FURTHER INFORMATION)		
DESCRIPTION	THREAD SIZE	QTY
LUBE QUILL (LQX)	1/4 NPT (F)	1
LUBE POINTS (LPx)	1/4 NPT (F)	6
SEAL SUPPLY (LBI-A)	1/2 NPT (F)	1
SEAL RETURN (LBO-A)	1/2 NPT (F)	1

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES. TOLERANCES: ANGULAR: MACH 2 DEG. SURFACE FINISH: 125 RAO FLAT FACE DIMENAL. 1.000 THIRD PLACE DECIMAL. 1.000 THIRD PLACE DECIMAL. 1.000

PROPERTY AND CONFIDENTIAL

Ro-Flo COMPRESSORS

GENERAL ARRANGEMENT, 7D, DBS, CW

16-123-633-402 12

SCALE: 1:3 510 LBS 1 OF 1