



- NOTES:
- CENTER OF MASS DIMENSIONS ARE APPROXIMATE
 - EITHER WATER INLET MAY BE USED, DEPENDING UPON SYSTEM NEEDS
 - WEIGHT IS APPROXIMATE
 - USE SEAL OIL RETURN PORT AS SHOWN IN TOP VIEW

SEAL LIQUID BARRIER CONNECTIONS			QTY.
LBI	SEAL LIQUID BARRIER INLET	1/2 NPT(F)	1
LBO	SEAL LIQUID BARRIER OUTLET	1/2 NPT(F)	1

NOZZLE CONNECTIONS		BOLT HOLE SIZE
N1	4" GAS SUCTION FLANGE (ANSI CLASS 150 FLAT FACE)	8 x 5/8-11 ∇ 1.00
N2	3" GAS DISCHARGE FLANGE (ANSI CLASS 150 FLAT FACE)	4 x 5/8-11 ∇ 1.00
W1A	2 NPT(F) WATER INLET (SEE NOTE 2)	N/A
W1B	1-1/2 NPT(F) WATER INLET (SEE NOTE 2)	N/A
W2	1-1/4 NPT(F) WATER OUTLET	N/A
D1	1/2 NPT (F) DRAIN HOLE	N/A
D2	1/2 NPT (F) DRAIN HOLE	N/A

LUBRICATION OIL CONNECTION		
(REFER TO MANUAL FOR FURTHER INFORMATION)		
DESCRIPTION	THREAD SIZE	QTY
LUBE QUILL(LQ)	1/4 NPT(F)	1
LUBE POINTS(LPx)	1/4 NPT(F)	6

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES. TOLERANCES: ANGULAR: MACH 1 DEG. ONE PLACE DECIMAL. 1.500 TWO PLACE DECIMAL. 1.000 THREE PLACE DECIMAL. 0.010. INTERFERE GEOMETRIC TOLERANCING PER: ASME Y14.5M-2009. PROPERTIES AND CONVERSIONS: GENERAL ARRANGEMENT, 8DE, CCW, DBS. E 16-123-633-424 07. SCALE: 1:4. 800 LBS. SHEET 1 OF 1.