



OIL CONNECTION POINTS SUMMARY		
(REFER TO MANUAL FOR FURTHER INFORMATION)		
DESCRIPTION	THREAD SIZE	QTY
LUBE QUILL (LQx)	1/4 NPT (F)	1
LUBE POINTS (LPx)	1/4 NPT (F)	8
SEAL SUPPLY (LBI-A)	1/2 NPT (F)	1
SEAL RETURN (LBO-A)	1/2 NPT (F)	1

NOZZLE CONNECTIONS	BOLT HOLE SIZE
N1 8" GAS SUCTION FLANGE (ANSI CLASS 150 FLAT FACE)	8 x 3/4-10 [1.12]
N2 6" GAS DISCHARGE FLANGE (ANSI CLASS 150 FLAT FACE)	8 x 3/4-10 [1.12]
W1A 2 NPT (F) WATER INLET (SEE NOTE 2)	N/A
W1B 2 NPT (F) WATER INLET (SEE NOTE 2)	N/A
W2 2 NPT (F) WATER OUTLET	N/A
D1 1/2 NPT DRAIN HOLE	N/A
D2 1/2 NPT DRAIN HOLE	N/A

- NOTES:
- CENTER OF MASS DIMENSIONS ARE APPROXIMATE
 - EITHER WATER INLET MAY BE USED, DEPENDING UPON SYSTEM NEEDS
 - WEIGHT IS APPROXIMATE
 - DRAWING IS DUAL DIMENSION. DIMENSIONS WITHOUT BRACKETS ARE IN INCHES DIMENSIONS IN [BRACKETS] ARE IN MILLIMETERS.
 - USE SEAL OIL RETURN PORT (LBO) AS SHOWN IN TOP VIEW.

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES UNLESS INDICATED. ANGULAR TOLERANCES: 1 PLACE DECIMAL, 10 MIN. 2 PLACE DECIMAL, 10 MIN. 3 PLACE DECIMAL, 10 MIN. 4 PLACE DECIMAL, 10 MIN. 5 PLACE DECIMAL, 10 MIN. INTERFERING GEOMETRIC TOLERANCING PER: ASME Y14.5-2009. PROPERTIES AND CONVERSIONS: GENERAL ARRANGEMENT, 17S,DBS,CCW. 16-123-633-430 10 1:6 3500 LBS. 1 OF 1

Ro-Flo COMPRESSORS

PROPERTY AND CONVERSIONS: GENERAL ARRANGEMENT, 17S,DBS,CCW. 16-123-633-430 10 1:6 3500 LBS. 1 OF 1