



- NOTES:
- CENTER OF MASS DIMENSIONS ARE APPROXIMATE
 - EITHER WATER INLET MAY BE USED, DEPENDING UPON SYSTEM NEEDS
 - WEIGHT IS APPROXIMATE
 - THIS DRAWING IS DUAL DIMENSION. DIMENSIONS WITHOUT BRACKETS ARE IN INCHES, DIMENSIONS IN [BRACKETS] ARE IN MILLIMETERS.
 - REMOVE (3) RED SEAL LOCKING TABS BEFORE OPERATION. RETAIN TABS AND SCREWS FOR SERVICE (TABS MUST BE INSTALLED BEFORE SEAL REMOVAL).

NOZZLE CONNECTIONS	BOLT HOLE SIZE
N1 3" GAS SUCTION FLANGE (ANSI CLASS 150 FLAT FACE)	4 x 5/8-11 ∇ 1.00
N2 3" GAS DISCHARGE FLANGE (ANSI CLASS 150 FLAT FACE)	4 x 5/8-11 ∇ 1.00
W1A 1-1/4 NPT(F) WATER INLET (SEE NOTE 2)	N/A
W1B 1/2 NPT(F) WATER INLET (SEE NOTE 2)	N/A
W2 1-1/4 NPT(F) WATER OUTLET	N/A
D1 1/4 NPT(F) DRAIN HOLE	N/A
D2 1/8 NPT (F) SEAL WEEPAGE DRAIN	N/A

OIL CONNECTION POINTS SUMMARY		
(REFER TO MANUAL FOR FURTHER INFORMATION)		
DESCRIPTION	THREAD SIZE	QTY
LUBE QUILL (LQx)	1/4 NPT (F)	1
LUBE POINTS (LPx)	1/4 NPT (F)	6

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES (DIMENSIONS ARE IN MILLIMETERS) ANGULAR MATCH-5 DEG ONE PLACE DECIMAL (ONE PLACE DECIMAL) THREE PLACE DECIMAL (THREE PLACE DECIMAL) UNLESS OTHERWISE SPECIFIED: TOLERANCES PER ASME

DATE: 12/29/2022
 CHECKED: TSS
 DRAWN: TRF
 TITLE: GENERAL ARRANGEMENT, 7D, SC, CW

Ro-Flo COMPRESSORS

16-123-634-503 00

1:3 510 LBS 1 OF 1