





OIL CONNECTION POINTS SUMMARY				
(REFER TO MANUAL FOR FURTHER INFORMATION)				
DESCRIPTION	THREAD SIZE	QTY		
LUBE QUILL(LQx)	1/4 NPT (F)	1		
LUBE POINTS (LPx)	1/4 NPT (F)	8		

N1	8" GAS SUCTION FLANGE (ANSI CLASS 150 FLAT FACE)	8 x 3/4-10√ 1.12
N2	6" GAS DISCHARGE FLANGE (ANSI CLASS 150 FLAT FACE)	8 x 3/4-10√ 1.12
W1A	2 NPT(F) WATER INLET (SEE NOTE 2)	N/A
W1B	2 NPT(F) WATER INLET (SEE NOTE 2)	N/A
W2	2 NPT(F) WATER OUTLET	N/A
D1	1/2 NPT DRAIN HOLE	N/A
D2	1/2 NPT DRAIN HOLE	N/A
D3	1/8 NPT SEAL WEEPAGE HOLE	N/A

NOZZLE CONNECTIONS

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES TOLERANCES:
ANGULAR: MACH ± .5 DEG ONE PLACE DECIMAL ± .060 TWO PLACE DECIMAL ± .030 THREE PLACE DECIMAL ± .010
INTERPRET GEOMETRIC

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF RO-FLO COMPRESSORS, LLC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF RO-FLO COMPRESSORS, LLC. IS PROHIBITED.

1.6 WEIGHT:

SCALE:

1.6 WEIGHT:

SHEET:

1.6 SIZE

PART NO.

REV

16-123-634-513

O

SCALE:

1.6 WEIGHT:

3500 LBS

SHEET:

1.6 I

BOLT HOLE SIZE

1:6 3500 LBS. SHEET: 1 OF 1

3. WEIGHT IS APPROXIMATE

2. EITHER WATER INLET MAY BE USED, DEPENDING UPON SYSTEM NEEDS

- - CENTER OF MASS DIMENSIONS ARE APPROXIMATE

NOTES:

4. THIS DRAWING IS DUAL DIMENSION. DIMENSIONS WITHOUT BRACKETS ARE IN INCHES, DIMENSIONS IN [BRACKETS] ARE IN MILLIMETERS.

5. REMOVE (3) RED SEAL LOCKING TABS BEFORE OPERATION. RETAIN TABS AND SCREWS FOR SERVICE (TABS MUST BE INSTALLED BEFORE SEAL REMOVAL).

THIS IS A LIFTING HOLE FOR CYLINDER HEAD (MAINTENANCE) ONLY.

DO NOT USE THIS HOLE FOR LIFTING COMPRESSOR!