

5

6

7


F

E

D

А

8



4

- REMOVE (3) RED SEAL LOCKING TABS BEFORE OPERATION. RETAIN TABS AND SCREWS FOR SERVICE (TABS MUST BE INSTALLED BEFORE SEAL REMOVAL).

3

DESCRIPTION	THREAD SIZE	QTY	REV
BE QUILL(LQx)	1/4 NPT (F)	2	16-123-634-516
BE POINTS(LPx)	1/4 NPT (F)	8	16-123

	NOZZLE CONNECTIONS	BOLT HOLE SIZE		
	10'' GAS SUCTION FLANGE (ANSI CLASS 150 FLAT FACE)	12 x 7/8-9⊽ 1.38		
	8'' GAS DISCHARGE FLANGE (ANSI CLASS 150 FLAT FACE)	8 x 3/4-10⊽ 1.12		
4	2 NPT(F) WATER INLET (SEE NOTE 2)	N/A		
3	2 NPT(F) WATER INLET (SEE NOTE 2)	N/A		
)	2 NPT(F) WATER OUTLET	N/A		
	1/2 NPT (F) DRAIN HOLE	N/A		
	1/2 NPT (F) DRAIN HOLE	N/A		
	1/8 NPT (F) SEAL WEEPAGE DRAIN	N/A		

UNLESS OTHERWISE SPECIFIED:		NAME	DATE	_					•
DIMENSIONS ARE IN INCHES TOLERANCES:	DRAWN	TRF	11/17/2022	7				-F	
ANGULAR: MACH ±.5 DEG	CHECKED	TSS	11/17/2022						
ONE PLACE DECIMAL ±.060	ENG APPR.	BTS	11/17/2022				COMPR	ESSOR	s ==
TWO PLACE DECIMAL ±.030 THREE PLACE DECIMAL ±.010	PROPRIETARY AND CONFIDENTIAL		TITLE:		-RAL			FNIT	
INTERPRET GEOMETRIC TOLERANCING PER: ANSI		THE INFORMATION CONTAINED IN THIS			GENERAL ARRANGEMENT, 19L,SC,CW				
MATERIAL	DRAWING IS	S THE SOLE PR	OPERTY OF	SIZE	PART N		,,.		REV
FINISH(UNLESS OTHERWISE NOTED)	REPRODUC WITHOUT TH		OR AS A WHOLE RMISSION OF	Ε	16-	-123-	-634-	-516	00
	PROHIBITED			SCALE:	1:8	WEIGHT:	50 LBS.	SHEET:	OF 1

2