



 $3/4-10 \text{ UNC} - 2B \ \sqrt{} .75[19.05]$ THIS IS A LIFTING HOLE FOR CYLINDER HEAD (MAINTENANCE) ONLY.
DO NOT USE THIS HOLE FOR LIFTING COMPRESSOR!

NOTES:

- 1. - CENTER OF MASS DIMENSIONS ARE APPROXIMATE
- 2. EITHER WATER INLET MAY BE USED, DEPENDING UPON SYSTEM NEEDS
- 3. WEIGHT IS APPROXIMATE
- 4. THIS DRAWING IS DUAL DIMENSION. DIMENSIONS WITHOUT BRACKETS ARE IN INCHES, DIMENSIONS IN [BRACKETS] ARE IN MILLIMETERS.
- 5. REMOVE (3) RED SEAL LOCKING TABS BEFORE OPERATION. RETAIN TABS AND SCREWS FOR SERVICE (TABS MUST BE INSTALLED BEFORE SEAL REMOVAL).

	NOZZLE CONNECTIONS	BOLT HOLE SIZE
N1	10" GAS SUCTION FLANGE (ANSI CLASS 150 FLAT FACE)	12 x 7/8-9
N2	8" GAS DISCHARGE FLANGE (ANSI CLASS 150 FLAT FACE)	8 x 3/4-10√ 1.12
W1A	2 NPT(F) WATER INLET (SEE NOTE 2)	N/A
W1B	2 NPT(F) WATER INLET (SEE NOTE 2)	N/A
W2	2 NPT(F) WATER OUTLET	N/A
D1	1/2 NPT(F) DRAIN HOLE	N/A
D2	1/2 NPT(F) DRAIN HOLE	N/A
D3	1/8 NPT(F) SEAL WEEPAGE DRAIN	N/A

LUBRICATION OIL CONNECTION							
(REFER TO MANUAL FOR FURTHER INFORMATION)							
DESCRIPTION	THREAD SIZE	QTY					
LUBE QUILL(LQx)	1/4 NPT(F)	2					
LUBE POINTS (LPx)	1/4 NPT(F)	8					

	UNLESS OTHERWISE SPECIFIED:		NAME	DATE		1	
	DIMENSIONS ARE IN INCHES TOLERANCES:	DRAWN	TRF	11/10/2022	7		
ANG	ANGULAR: MACH±.5 DEG	CHECKED	TSS	11/10/2022	(
	ONE PLACE DECIMAL ±.060	ENG APPR.	BTS	11/10/2022	`		
	TWO PLACE DECIMAL ±.030 THREE PLACE DECIMAL ±.010	PROPRIE	GFI	VIE			
	INTERPRET GEOMETRIC TOLERANCING PER: ANSI	THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF RO-FLO COMPRESSORS LLC. ANY			OLINLI		
	MATERIAL				SIZE	PART	
	FINISH(UNLESS OTHERWISE NOTED)	REPRODUCT	E	14			

ERAL ARRANGEMENT, 19LE, CW, SC REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF RO-FLO COMPRESSORS, LLC. IS PROHIBITED.

1:8 5375 LBS SHEET: 1 OF 1