

- ARE IN INCHES, DIMENSIONS IN [BRACKETS] ARE IN MILLIMETERS.

5. REMOVE (3) RED SEAL LOCKING TABS BEFORE OPERATION. RETAIN TABS AND SCREWS FOR SERVICE (TABS MUST BE INSTALLED BEFORE SEAL REMOVAL).

		Ň			F
	0				
		1) of			
		0			
	A C				
_					
		8			E
//					
	[951.7]				
	37.47				D
	[174.6]				
	[174.6] 6.88				
	-				С
	I				
	OIL CONNECTION POINTS SUMMARY (REFER TO MANUAL FOR FURTHER INFORMATION)				
-	DESCRIPTION	THREAD S			REV 00
-	LUBE QUILL(LQx)	1/4 NPT (F)	NONE	16-123-634-540 C
-	LUBE POINTS (LPx)	1/4 NPT (F)	8	16-123-
					Ш
NOZZLE CONNECTIONS BOLT HOLE SIZ					
	6" GAS SUCTIO (ANSI CLASS 150		8 x 3	3/4-10∓1.12	
2	5" GAS DISCHAR (ANSI CLASS 150	GE FLANGE FLAT FACE)	8 x 3	3/4-10∓1.12	
A	2 NPT(F) WATER INLET (SEE NOTE 2)		N/A		_
В	2 NPT(F) WATER INLET (SEE NOTE 2)		N/A		
2	2 NPT(F) WATER OUTLET		N/A		_
	1/2 NPT(F) DRAIN HOLE		N/A		_
2	1/2 NPT(F) DRAIN HOLE 1/8 NPT (F) SEAL WEEPAGE		N/A		A
כ	DRAIN			N/A	
	UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES TOLERANCES: DRAWN	NAME DATE TRF 7/3/2018		Ro-Flo	
	ANGULAR: MACH ±.5 DEG ONE PLACE DECIMAL ±.060 TWO PLACE DECIMAL ±.030 THREE PLACE DECIMAL ±.010 INTERPRET GEOMETRIC	TSS 7/3/2018 BTS 7/3/2018 TARY AND CONFIDENTIAL		ECOMPRESSORS	
	TOLERANCING PER: ANSI MATERIAL FINISH (UNLESS OTHERWISE NOTED) THE INFORM DRAWING IS RO-FLO CO REPRODUCT WITHOUT TH	ATION CONTAINED IN THIS THE SOLE PROPERTY OF MPRESSORS,LLC. ANY TION IN PART OR AS A WHOLE E WRITTEN PERMISSION OF MPRESSORS, LLC. IS	PART NO.	L, CCW, SC 23-634-540 00	
	RO-FLO CO PROHIBITED.		1:5	7: 2000 LBS. 1 OF 1	

 \bigcirc