

5

6

7

8

4

| OIL CONNECTION POINTS SUMMARY<br>(REFER TO MANUAL FOR FURTHER INFORMATION) |             |     |  |
|--|-------------|-----|--|
| DESCRIPTION  | THREAD SIZE | QTY |  |
| LUBE QUILL(LQx)  | 1/4 NPT (F) | 1   |  |
| LUBE<br>POINTS (LPx)   | 1/4 NPT (F) | 4   |  |

N2 W1A W1B W2 D1

2

5. REMOVE (3) RED SEAL LOCKING TABS BEFORE OPERATION. RETAIN TABS AND SCREWS FOR SERVICE (TABS MUST BE INSTALLED BEFORE SEAL REMOVAL).

3

| .9]<br>0<br>[339.5]<br>13.37                |  |
|---|--|
|   | [131.8]<br>5.19<br>0<br>0<br>0<br>0<br>0<br>0<br>0<br>0<br>0<br>0<br>0<br>0<br>0<br>0<br>0<br>0<br>0<br>0<br>0 |
| NOZZLE CONNECTIONS<br>2" GAS SUCTION FLANGE | BOLT HOLE SIZE   |
| (ANSI CLASS 150 FLAT FACE)                  | 4 x 5/8-11   |

|   | 2" GAS SUCTION FLANGE<br>(ANSI CLASS 150 FLAT FACE)          | 4 x 5/8-11⊽1.00 |
|---|--|-----------------|
|   | 1.50'' GAS DISCHARGE<br>FLANGE (ANSI CLASS 150<br>FLAT FACE) | 4 x 1/2-13⊽.88  |
| ١ | 1 NPT(F) WATER INLET (SEE<br>NOTE 2)                         | N/A             |
| ) | 3/8 NPT(F) WATER INLET (SEE<br>NOTE 2)                       | N/A             |
|   | 1 NPT(F) WATER OUTLET  | N/A             |
|   | 1/4 NPT(F) DRAIN HOLE  | N/A             |
|   | 1/8 NPT(F) SEAL OIL<br>WEEPAGE DRAIN                         | N/A             |
|   |  |                 |

UNLESS OTHERWISE SPECIFIED: Ro-Flo COMPRESSORS NAME DATE DIMENSIONS ARE IN INCHES DRAWN TRF 12/28/2023 TOLERANCES: CHECKED TSS 12/28/2023 ANGULAR: MACH±.5 DEG ONE PLACE DECIMAL ±.040 TWO PLACE DECIMAL ±.030 THREE PLACE DECIMAL ±.030 INTERPRET GEOMETRIC TOLERANCING PER: ANSI MATERIAL COMPRESSORS.LC. ANY PEPERPODUCTION IN PAPET OR AS A GENERAL ARRANGEMENT, 4CC,SC,CCW FINISH(UNLESS OTHERWISE NOTED) WITHOUT THE WRITTEN PERMISSION OF RO-FLO COMPRESSORS, LLC. IS PROHIBITED. VIEIGHT: SHEET: 1 OF 1 1:2 WEIGHT: SHEET: 1 OF 1